

■ **High solids**

■ **Durable**



■ **Excellent for all indoor wood surfaces**

BENCH MAINTENANCE

4 Ease

TECHNICAL DATA SHEET


Highlights

- Penetrates
- Lubricates
- Displaces moisture
- Prevents corrosion

SAFETY CAUTIONS

- Keep out of reach of children.
- Contents under pressure. Do not expose to heat or store at temperatures exceeding 120° F. Do not use near sparks or open flames. Do not puncture or incinerate container. Wrap empty container and put in trash collection.
- Refer to M.S.D.S. for additional safety information.

HMIS RATING



DIRECTIONS

Penetrating Oil frees rusted and corroded nuts, bolts, studs, set screws, aluminum and copper fittings. Penetrating Oil also lubricates and prevents corrosion on rusted and frozen parts. Can be used on most metal, wood and painted surfaces. Use Penetrating Oil in garages, factories, on farm machinery, marine and aeronautical equipment, in shops and homes.

DIRECTIONS:

- Hold container upright 6 to 8 inches from surface to be sprayed.
- Spray area to be treated liberally and allow sufficient time for complete penetration.
- Repeat treatment on extremely corroded parts.
- Tapping or heating may be required in some severe instances.

USDA: Authorized by USDA for use in federally inspected meat and poultry plants.

DANGER: DANGER! Extremely flammable. Avoid breathing vapor. Harmful or fatal if swallowed. Use only with adequate ventilation.

TYPICAL PROPERTIES

- Specific Gravity: **0.798**
- Propellant: **Hydrocarbon**
- Spray Characteristics: **Streamy spray**
- Appearance: **Clear amber liquid**
- Odor: **Petroleum distillates**
- Net Weight: **15 ounces**
- USDA: **H-2**



Globe Chemical Co., Inc.
2833 Washington Street
Avondale Estates, Georgia 30002

"Quality is Our Most Important Product"