



RED HOT

Description Red Hot Sewer Solvent is a strong alkaline compound used in opening sewers and drains by reacting quickly on grease, rags, paper, and other organic material. Heats up rapidly and "burns" for several minutes. Outstanding for use as a preventative maintenance product that will save time, labor, and money.

Directions Pour a small amount (4 oz. per gallon) in the drain keeping face away from the drain. If plunger is used, make sure all precautions are taken to avoid injury. After 15 minutes run plenty of water through drain.

Safety It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Keep Out Of Reach Of Children. Refer to Material Safety Data Sheet for additional information.

Active Properties

- Temperature of 20% aqueous solution - 215 deg. F. minimum
- Time to reach maximum temperature - 1 min 30 sec maximum
- Time to sustain temperature of 180 deg. F. - 7 minutes minimum

SPECIFICATIONS

- Sodium Hydroxide (Granulated Caustic) 67%
- Type Material granular
- Aluminum 8%
- Bulk Density 72-80 lbs/ft
- pH (1% solution) 12.9 - 13.2
- Appearance red granular

**GLOBE CHEMICAL COMPANY
2833 WASHINGTON STREET
AVONDALE ESTATES, GEORGIA 30002**