

NON-CHLORINATED AUTOMOTIVE SILICONE

Quality is Our Most Important Product



SILICONE

Description

A never dry silicone lubricating film developed exclusively for the automotive and other vehicle maintenance industry. Lubricates and restores life of molding and weather stripping of doors and trunk seals. Stops annoying squeaks and binding of door, hood and trunk hinges and window tracking.

For Use By

NEW CAR DEALERSHIPS
AUTO REPAIR SHOPS
MUNICIPAL GARAGES
FLEET OPERATORS
AUTO RESTORERS
USED CAR REFURNISHING

For Use On

DOOR AND TRUNK SEALS
DOOR, HOOD AND TRUNK HINGES
WINDOW TRACKING AND CRANKS
EMERGENCY BRAKE CABLES
LOCK MECHANISMS
TIRE DRESSING

Features

QUICK PENETRATION INTO HINGES AND RUBBER MOLDING

SILICONE LUBRICANT PROVIDES
WEATHER RESISTANT LONG TERM PROTECTION

PREVENTS DRYING AND CRACKING OF RUBBER PARTS

Specifications

Appearance and Odor	Clear Liquid / Solvent Odor
Flash Point of Concentrate	80°F T.O.C.
Aerosol Flammability	Flammable Spray
Specific Gravity of Concentrate	0.820
Propellant	Hydrocarbon
NFPA-30B Classification	Level 3 Aerosol
Packaging	12 X 12oz. Net Wt. cans per case (16oz. Size Cans)

SEE MSDS AND LABEL FOR PRECAUTIONARY AND HEALTH HAZARD INFORMATION