

■ **High solids**

■ **Durable**



■ **Excellent for all indoor wood surfaces**

STOP BELT SLIPPAGE

BELT DRESSING

TECHNICAL DATA SHEET


Highlights

- Stops belt slippage
- Does not attract dirt or dust

SAFETY CAUTIONS

- Keep out of reach of children.
- Contents under pressure. Do not expose to heat or store at temperatures exceeding 120° F. Do not use near sparks or open flames. Do not puncture or incinerate container. Wrap empty container and put in trash collection.
- Refer to M.S.D.S. for additional safety information.

HMIS RATING



DIRECTIONS

This product will not glaze and does not attract dirt or dust. The coating prevents slippage on belts exposed to outdoor as well as indoor environmental conditions. Effective on all belts and belting materials.

Use on: "V", flat or round belts made of leather, rubber, fabric or synthetic material.

Note: In many instances protective guards must be removed in order to apply this product properly. In such cases please use extreme care to prevent accidents. Be sure to replace guards after treatment.

DIRECTIONS:

- Apply a little at a time to inner surface of belt while machinery is in motion.
- Spray using a back and forth motion until the surface is completely wet.
- On most belts, the spray may be applied to the sheaves, pulleys, or directly onto the belt itself.
- Repeat occasionally to maintain full power and to optimize belt life.

DANGER: Flammable. Use only in a well ventilated area. Vapor harmful. Harmful or fatal if swallowed. Avoid contact with eyes or prolonged contact with skin.

TYPICAL PROPERTIES

- Specific Gravity: 0.814
- Propellant: Hydrocarbon
- Spray Characteristics: **Narrow stream, with extension tube**
- Appearance: **Clear, amber liquid**
- Odor: **Alcohol**
- Net Weight: **15 ounces**
- USDA: **P-1**



Globe Chemical Co., Inc.
2833 Washington Street
Avondale Estates, Georgia 30002

"Quality is Our Most Important Product"