

USE BRAKE  
BRAKE SQUEAL.  
BRAKE FLUID, OIL AND  
WITHOUT

PADS, BACKING PLATES, DRUMS,  
AND RELATED BRAKE PARTS. CAN  
BEFORE PAINTING, WELDING, OR  
COMPOUNDS.

BEFORE USING.  
ALLOW PRODUCT TO RUN OFF.  
CLOTH.  
NECESSARY.

## BENEFITS

QUICKLY AND LEAVES

- ❖ PROVIDES A POWERFUL FLUSHING ACTION WHICH BLASTS AWAY TOUGH, THICK GREASE AND GRIME.
- ❖ REMOVES HARMFUL WATER AND CONDENSATION FROM PARTS BEING CLEANED.
- ❖ PARTS DRY QUICKLY AND CAN BE ASSEMBLED IMMEDIATELY WITH NO FILM OR RESIDUE LEFT ON THE PARTS AFTER CLEANING.

## SPECIFICATIONS

APPEARANCE:	CLEAR
ODOR:	SOLVENT
PROPELLANT:	CO <sub>2</sub>
V.O.C.:	77.6%
NFPA 714 - FLAMMABILITY:	1
NFPA 30B - STORAGE:	1
CAN SIZE/LABEL WT.:	20 oz./18 oz.

data sheet

