

Quality is Our Most Important Product



CUSTOMER SERVICE BULLETIN

FLOAT

FLOATING GREASE AND SCUM SOLVENT SEWAGE DIGESTER

DESCRIPTION:

This product is a floating grease and scum solvent which will find use as a sewage digester. It may be used for grease traps, pumping stations, wet wells and sewer lines. This product consists of a blend of aliphatic hydrocarbons of petroleum and non-petroleum origin and is a combustible liquid which must be protected from sources of ignition. It is a solvent for removal of many printing inks, rosins, ester gums, alkyd resins, tar and asphalt. It should be tested on an inconspicuous area before using on painted surfaces.

USES:

For Grease Traps:

1. Start treatment immediately after the grease trap has been pumped. Add one quart per cubic foot of capacity, then begin preventive maintenance schedule one week later. Repeat procedure after pumping.
- For traps where scum blankets & grease cakes have already formed add one gallon per cubic foot directly to the grease trap. Repeat every 3 to 4 days until the scum blanket is liquefied.

Preventative Maintenance:

One (1) gallon daily per 40 cubic feet of trap capacity.

For Pumping Stations, Wet Wells and Sewer Lines:

Add 1% - 5% by volume (i.e. 1-5 gallons per 100 gallons of capacity) as initial treatment. For preventive maintenance (daily application) use 0.25% (i.e. 1 quart per 100 gallons of capacity).

TECHNICAL DATA:

Physical Appearance	Thin Liquid
Color	Green
Odor	Citrus
Specific Gravity	0.80 ± 0.02
Pounds per Gallon	6.7 ± 0.1
pH (concentrate)	N/A
Brookfield Viscosity @ 20 Degrees C	4 cps
MSA Authorization	N/A

4390/020689