

■ **High solids**

■ **Durable**



■ **Excellent for all indoor wood surfaces**

BENCH MAINTENANCE

Open Gear Aerosol

TECHNICAL DATA SHEET


Highlights

- Very tacky - does not slip off
- Effective at high temperatures
- Protects against excessive wear
- Inhibits corrosion

SAFETY CAUTIONS

- Keep out of reach of children.
- Contents under pressure. Do not expose to heat or store at temperatures exceeding 120° F. Do not use near sparks or open flames. Do not puncture or incinerate container. Wrap empty container and put in trash collection.
- Refer to M.S.D.S. for additional safety information.

HMIS RATING



DIRECTIONS

OPEN GEAR LUBE is an extremely tacky wear resistant lubricant. Resistant to water. Perfect for construction equipment, gears, sprockets, slow moving chains, and machinery. Prevents corrosion and resists oxidation by repelling moisture. It is perfect for 5th wheels due to its wear resistance and adhesion. Reduces down time and noise due to metal to metal contact. Provides a smooth and uniform coating for excellent lubricity and corrosion protection on machinery and various metal parts and equipment.

DIRECTIONS

Shake well before using. Remove protective cap. Hold can 6 to 8 inches from surfaces to be sprayed. Apply an even coat to surface. Turn on machinery and allow lubricant to spread over all working surfaces. Apply a second thinner coating to insure adequate lubrication. Reapply as needed to lubricate and protect equipment. After spraying turn can upside down and spray until nozzle is clear.

TYPICAL PROPERTIES

- Specific Gravity: **0.86**
- Propellant: **Hydrocarbon**
- Spray Characteristics: **Coarse spray**
- Appearance: **Dark liquid**
- Odor: **Solvent**
- Net Weight: **12 ounces**