

■ **High solids**

■ **Durable**



■ **Excellent for all indoor wood surfaces**

BENCH MAINTENANCE

Oven Pro Aerosol

TECHNICAL DATA SHEET


Highlights

- Fine spray pattern for uniform application
- Flexible coating
- Inhibits corrosion
- Moisture resistant

SAFETY CAUTIONS

- Keep out of reach of children.
- Contents under pressure. Do not expose to heat or store at temperatures exceeding 120° F. Do not use near sparks or open flames. Do not puncture or incinerate container. Wrap empty container and put in trash collection.
- Refer to M.S.D.S. for additional safety information.

HMIS RATING



DIRECTIONS

This translucent coating is to be used similar to cosmoline. It is sprayed over a wide area to inhibit rust and weathering on metal parts. Excellent for use on parts being stored or for newly manufactured metal parts to be shipped. The translucent coating allows for markings and other information printed on the parts to still be seen through the coating.

DIRECTIONS

Product is most effective when parts are clean and free of rust, scale or dirt. However, product will afford adequate protection when applied over rust, scale, and dirt, and will aid in removal later.

Remove protective cap. Point opening in spray tip towards part to be coated. Holding can 8 to 10 inches from part, spray 2 or 3 mil coat with a slow sweeping motion. Completely wet surface. For extremely severe conditions, wait 5 minutes and apply another coat. Product will completely set up in 2 hours. Once the film is hard, part can be handled. Dust and dirt can be wiped off without affecting film.

TYPICAL PROPERTIES

- Specific Gravity: **0.78**
- Propellant: **Hydrocarbon**
- Spray Characteristics: **Fine spray**
- Appearance: **Brown Liquid**
- Odor: **Solvent**
- Net Weight: **12 ounces**

